# PCT/EP 03 /24 9 0 0



Europäisches **Patentamt** 

European **Patent Office** 

Office européen des brevets

Bescheinigung

Certificate

REC'D 2 1 MAR 2003 PCT

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application conformes à la version described on the following page, as originally filed.

Les documents fixés à cette attestation sont initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr.

Patent application No. Demande de brevet nº

02405170.8

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b) Der Präsident des Europäischen Patentamts;

For the President of the European Patent Office

Le Président de l'Office européen des brevets p.o.

R C van Dijk

DEN HAAG, DEN THE HAGUE, LA HAYE, LE

FPA/FPO/OFR Form

13/12/02

1014

- 02 91

**BEST AVAILABLE COPY** 



#### Europäisches Patentamt

# European Patent Office

## Office européen des brevets

### Blatt 2 der Bescheinigung Sheet 2 of the certificate Page 2 de l'attestation

Anmeldung Nr.: Application no.: Demande n°:

plication no.: 02405170.8

Anmeldetag: Date of filing: Date de dépôt:

06/03/02

Anmelder: Applicant(s): Demandeur(s):

Ciba Specialty Chemicals Holding Inc.

4057 Basel SWITZERLAND

Bezeichnung der Erfindung: Title of the invention: Titre de l'invention:

Heat sensitive recording material

In Anspruch genommene Prioriät(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat: State: Pays: Tag: Date: Aktenzeichen: File no. Numéro de dépôt:

Internationale Patentklassifikation: International Patent classification: Classification Internationale des brevets:

B41M5/30

Am Anmeldetag benannte Vertragstaaten: Contracting states designated at date of filing: Etats contractants désignés lors du depôt:

AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR

Bemerkungen: Remarks; Remarques;

#### **Heat Sensitive Recording Material**

The present invention relates to a heat sensitive composition, a heat sensitive recording material comprising this composition and the use of this composition as heat-sensitive coloured image-forming layer in heat-sensitive materials.

Usually heat sensitive recording material comprises a supporting substrate, for example, a paper sheet, synthetic paper sheet or plastic resin film, and a thermosensitive coloured image-forming layer formed on a surface of the supporting substrate and comprising a colourless or pale coloured electron donative compound (colour forming compound or sometimes called colourless dye precursor), an organic electron acceptor (developer), and a binder.

Heat sensitive recording has conventionally been used as a system for recording transferred information through the mediation of heat, by utilizing a colour reaction between a colour forming compound and a developer.

The properties which are most desirable in a colour forming material, in addition to the effective development of colour, are thermal response, background whiteness and image stability, especially light fastness of the developed colour, heat and moisture fastness of the developed colour, oil fastness of the developed colour, plasticiser resistance of the developed colour and water fastness of the developed colour. In order to achieve these goals, it is known, for example, to add sensitizers to improve the performance of the heat sensitive composition with respect to the rate of image formation and to add stabilizers to improve resistance to oily and fatty substances and plasticisers.

For example, EP-A 620 122 discloses a thermosensitive recording material in which as a sensitizing additive an aromatic amide is used.

EP-A 535 887 describes a thermosensitive recording material which comprises a colour developing agent having at least two sulfonyl(thio)urea units per molecule. According to the specification (p. 9, l. 15-21), the amount of either this colour developing agent or of any

other conventional colour developing compound is at least 5% in order to avoid unsatisfactory colour-forming performance.

However, a disadvantage of heat sensitive recording materials is the stability of the image in that the reaction of the colour former with the colour-developing agent is reversible and thus the resultant coloured images fade particularly towards light over a prolonged period of time. In addition, the stability of the image is lowered when it is stored under severe conditions, for example at elevated temperatures and/or humidity, or when the recording material is brought into contact with water, an oily or fatty substance or plasticisers.

Therefore, a need still exists to improve the above properties and to improve the archival capabilities of such recording materials. In particular, it is an object of the present invention to provide a heat sensitive composition for use in heat sensitive recording materials with improved properties, especially to provide an increase in image stability whilst maintaining or improving the background whiteness of the paper before imaging and the background whiteness of the undeveloped portion after imaging.

Accordingly, the claimed composition has been found. In addition, a heat sensitive recording material has been found, too, as well as the use of compounds I to III as stabilizers in heat sensitive recording materials.

The present invention relates to a heat sensitive recording material comprising

- a) a colour former compound,
- b) a developer, which is different from the stabilizer used as component c),
- c) a stabilizer, selected from the group consisting of compounds having the formulae I, II and III,

$$R_1SO_2NHCNHR_2$$
 (I),  $(R_1SO_2NHCNH)_n-A$  (II)

and

$$R_{i} = S_{O} \stackrel{O}{\longrightarrow} N = N = Y_{1}$$
 (III)

wherein

 $R_1$  stands for unsubstituted or substituted phenyl or naphthyl,  $C_1$ - $C_{20}$ alkyl,  $C_3$ - $C_{10}$ cycloalkyl, wherein the carbon chains of the alkyl (i.e. at least two carbon atoms) and cycloalkyl groups may be interrupted by -O-, -S-, -NH-radicals, or unsubstituted or substituted aralkyl having from seven to twelve carbon atoms,

R<sub>2</sub> stands for hydrogen, unsubstituted or substituted phenyl, naphthyl, C<sub>1</sub>-C<sub>20</sub>alkyl, unsubstituted or substituted aralkyl having from seven to twelve carbon atoms, or R<sub>2</sub> stands for -R<sub>3</sub>-B-R<sub>4</sub>, in which R<sub>3</sub> stands for phenylene or naphthylene, in particular for o-, m- or p-phenylene, preferably p-phenylene, or 1,2; 2,3; 1,4 or 1,5-naphthylene, preferably 1,5-naphthylene, and wherein B stands for -O-SO<sub>2</sub>-, -SO<sub>2</sub>-O-, -NH-SO<sub>2</sub>-, -SO<sub>2</sub>-NH-, -S-SO<sub>2</sub>-, -O-CO-, -O-CO-NH-, -NH-CO-, -NH-CO-O-, -S-CO-NH-, -S-CS-NH-, -CO-NH-SO<sub>2</sub>-, -O-CO-, -NH-SO<sub>2</sub>-, -NH=CH-, -CO-NH-CO-, -S-, -CO-, -O-, -SO<sub>2</sub>-NH-CO-, -O-CO-O-, -CH<sub>2</sub>-, -CH<sub>2</sub>CH<sub>2</sub>-, -SO<sub>2</sub>-, -O-PO-(OR<sub>4</sub>)<sub>2</sub>, -CONH- and -COO-, preferably -O-SO<sub>2</sub>-, -SO<sub>2</sub>-O-, -SO<sub>2</sub>-NH-, -S-SO<sub>2</sub>-, -O-CO-, SO<sub>2</sub>-, -O-CO-NH-, -CONH-, -O- and -COO-, more preferably -O-SO<sub>2</sub>-, -SO<sub>2</sub>-, -O- and -COO-.

and R<sub>4</sub> stands for hydrogen, C<sub>5</sub>-C<sub>10</sub>aryl, preferably phenyl or naphthyl which can be unsubstituted or substituted one to three times by, for example, C,-Calkyl, halogensubstituted C<sub>1</sub>-C<sub>8</sub>alkyl, C<sub>1</sub>-C<sub>8</sub>alkoxy-substituted C<sub>1</sub>-C<sub>8</sub>alkyl, C<sub>1</sub>-C<sub>8</sub>alkoxy, halogen-substituted C,-C, alkoxy or halogen, preferred C,-C, alkyl and C,-C, alkoxy, preferred substituents are C,-C<sub>4</sub> alkyl and halogen, in particular preferred are phenyl which is unsubstituted or substituted by C,-C, alkyl, halogen-substituted C,-C, alkyl, C,-C, alkoxy-substituted C,-C, alkyl, C,-C, alkoxy, halogen-substituted C<sub>1</sub>-C<sub>2</sub>alkoxy or halogen, and unsubstituted naphthyl, more preferred are phenyl which is unsubstituted or substituted by C,-C,alkyl or halogen, and naphthyl, especially phenyl which is unsubstituted or substituted by C,-C,alkyl, benzyl, unsubstituted, preferred, or substituted one to three times by C,-C,alkyl, halogensubstituted C<sub>1</sub>-C<sub>8</sub>alkyl, C<sub>1</sub>-C<sub>8</sub>alkoxy-substituted C<sub>1</sub>-C<sub>8</sub>alkyl, C<sub>1</sub>-C<sub>8</sub>alkoxy, halogen-substituted C<sub>1</sub>-C<sub>n</sub> alkoxy or halogen, preferred is unsubstituted benzyl, or C<sub>1</sub>-C<sub>20</sub>alkyl, preferably C<sub>1</sub>-C<sub>8</sub>alkyl, more preferably C<sub>1</sub>-C<sub>6</sub>alkyl, most preferred C<sub>1</sub>-C<sub>4</sub>alkyl, which can be unsubstituted, preferred, or substituted one to three times by, for example, C,-C<sub>8</sub> alkoxy, halogen, preferred halogen-substituted C<sub>1</sub>-C<sub>6</sub> alkyl, more preferred halogensubstituted C<sub>1</sub>-C<sub>4</sub>alkyl, phenyl or naphthyl, preferred phenyl-substituted C<sub>1</sub>-C<sub>6</sub>alkyl, or naphthyl-substituted C<sub>1</sub>-C<sub>5</sub> alkyl,

A represents a multivalent group having a valency of 2, 3 or 4, n represents an integer of 2, 3 or 4, and X stands for oxygen or sulphur,

 $Y_1$  stands for a heterocyclic ring having from two to seven carbon atoms and from 1 to three atoms selected from the group consisting of oxygen, nitrogen and sulphur, which can be substituted one to three times with unsubstituted or substituted phenyl,  $C_1$ - $C_2$ 0 alkyl,  $C_1$ - $C_3$ 1 alkoxy, halogen or  $-SO_2R_6$ ,  $R_6$  stands for phenyl, which may be substituted one to three times with  $C_1$ - $C_4$ 1 alkyl, wherein the total number of carbon, oxygen, sulphur and nitrogen atoms of the heterocyclic ring is from 5 to 9,

and wherein the amount of the stabilizer is less than 5% by weight, based on the total weight of the composition.

In a preferred embodiment  $R_1$  as phenyl or naphthyl can be unsubstituted or substituted one to three times by, for example,  $C_1$ - $C_9$ alkyl, preferably  $C_1$ - $C_4$ alkyl,  $C_1$ - $C_8$ alkoxy, preferably  $C_1$ - $C_4$ alkoxy or halogen. In case  $R_1$  stands for naphthyl, it is preferably unsubstituted. In case  $R_1$  stands for phenyl, it is preferably substituted one, two or three times, especially by  $C_1$ - $C_8$ alkyl, preferably  $C_1$ - $C_4$ alkyl.

In another preferred embodiment  $R_1$  as  $C_1$  -  $C_{20}$  alkyl can be unsubstituted, preferred, or substituted one, two or three times by, for example  $C_1$ - $C_8$ alkoxy, preferred  $C_1$ - $C_4$ alkoxy, or halogen.

In another preferred embodiment,  $R_1$  stands for  $C_3$ - $C_{10}$ cycloalkyl. In still another embodiment,  $R_1$  stands for  $C_2$ - $C_{20}$ alkyl having at least one member selected from the group consisting of O, S and NH included in the backbone chain thereof, preferably it is unsubstituted, and in particular  $R_1$  stands for the ethoxyethyl group. In another preferred embodiment,  $R_1$  stands for aralkyl, preferably benzyl, which can be unsubstituted, preferred, or substituted one two or three times by, for example,  $C_1$ - $C_4$ alkoxy.

Preferably,  $R_1$  is phenyl, which is unsubstituted or substituted by  $C_1$ - $C_8$ alkyl,  $C_1$ - $C_8$ alkoxy or halogen. Particular preferred are the substituted phenyl groups. Most preferred are phenyl groups, which are substituted by  $C_1$ - $C_4$  alkyl, in particular methyl.

In a preferred embodiment,  $R_2$  as  $C_1$ - $C_2$ oalkyl can be unsubstituted, preferred, or substituted one, two or three times by, for example  $C_1$ - $C_8$ alkoxy, preferred  $C_1$ - $C_4$ alkoxy, or halogen. In another preferred embodiment,  $R_2$  stands for phenyl or naphthyl that can be unsubstituted or substituted one, two or three times by, for example,  $C_1$ - $C_8$  alkyl, preferred  $C_1$ - $C_4$ alkyl, halogen-substituted  $C_1$ - $C_8$  alkyl,  $C_1$ - $C_8$  alkoxy-substituted  $C_1$ - $C_8$  alkyl, halogen or phenyl. In case  $R_2$  stands for naphthyl, naphthyl is preferred unsubstituted. In case  $R_2$  stands for phenyl, the phenyl group is either unsubstituted or substituted by  $C_1$ - $C_8$  alkyl, preferably  $C_1$ - $C_4$ alkyl, halogen-substituted  $C_1$ - $C_8$  alkyl,  $C_1$ - $C_8$  alkoxy-substituted  $C_1$ - $C_8$  alkyl, halogen, or phenyl, especially  $C_1$ - $C_8$  alkyl, halogen-substituted  $C_1$ - $C_8$  alkyl, or halogen. Preferably,  $R_2$  stands for phenyl, which is unsubstituted or substituted one, two or three times by  $C_1$ - $C_4$  alkyl, or halogen. In case  $R_2$  stands for aralkyl, the aralkyl group can be unsubstituted, preferred, or substituted one, two or three times by, for example,  $C_1$ - $C_4$ alkyl,  $C_1$ - $C_4$ alkoxy, or halogen.

 $C_1$ - $C_{20}$ alkyl stands for methyl, ethyl, n-, i-propyl, n-, i-, sec.- or tert.-butyl, n-, i-, tert.-pentyl, n-hexyl, n-heptyl, n-octyl, 2-ethyl-hexyl, n-nonyl, n-decyl, n-undecyl, n-dodecyl, n-tridecyl, n-tetradecyl, n-pentadecyl, n-hexadecyl, n-heptadecyl, n-octadecyl, n-nonadecyl, n-eicosyl, preferably  $C_1$ - $C_8$ alkyl such as methyl, ethyl, n-, i-propyl, n-, i-, sec.- or tert.-butyl, n-, i-, tert.-pentyl, n-hexyl, n-heptyl, n-octyl, 2-ethyl-hexyl, more preferably for  $C_1$ - $C_8$ alkyl such as for methyl, ethyl, n-, i-propyl, n-, i-, sec.- or tert.-butyl, n-, i-, tert.-pentyl, n-hexyl, and most preferred for  $C_1$ - $C_8$ alkyl such as for methyl, ethyl, n-, i-propyl, n-, i-, sec.- or tert.-butyl.

 $C_1$ - $C_8$ alkoxy stands for methoxy, ethoxy, n-, i-propoxy, n-butoxy, n-pentoxy, n-hexoxy, n-hexoxy, n-octoxy, preferred  $C_1$ - $C_8$ alkoxy such as methoxy, ethoxy, n-, i-propoxy, n-butoxy.

 $C_3$ - $C_{10}$ cycloalkyl stands for cyclopropyl, cyclobutyl, cyclopentyl, cyclohexyl, cyclohexyl, cyclononyl or cyclodecyl, preferably cyclohexyl.

 $C_s$ - $C_{10}$ aryl stands for phenyl and naphthyl. Halogen stands for fluorine, chlorine, bromine or iodine, preferably for chlorine.

In a preferred embodiment of this invention the weight ratio of stabilizer to colour former is in the range of from 0.05:1 to 1:1, preferably from 0.1:1 to 0.7:1, most preferred 0.45:1 to 0.55:1, in particular 0.5:1.

The weight ratio of developer to colour former usually is chosen in the range of from 1:1 to 5:1, preferably from 2:1 to 3:1.

The stabilisers of formula I are exemplified by but not limited to: N-(p-toluenesulphonyl)-N'-phenylurea, N-(p-toluenesulphonyl)-N'-(o-tolyl)urea, N-(p-toluenesulphonyl)-N'-(m-tolyl)urea, N-(p-toluenesulphonyl)-N'-(p-tolyl )urea, N-(p-toluenesulphonyl)-N'-(p-n-butylphenyl)urea, N-(p-toluenesulphonyl)-N'-(o-chlorophenyl)urea, N-(p-toluenesulphonyl)-N'-(mchlorophenyl)urea, N-(p-toluenesulphonyl)-N'-(2,4-dichlorophenyl)urea, N-(p-toluenesulphonyl)-N'-benzylurea, N-(p-toluenesulphonyl)-N'-(l-naphthyl)urea, N-(ptoluenesulphonyl)-N'-[1 -(2-methylnaphthyl)]urea, N-(p-toluenesulphonyl)-N'-(odiphenyl)urea, N-(p-toluenesulphonyl)-N'-butylurea, N-(benzenesulphonyl)-N'-phenylurea, N-(p-chlorobenzenesulphonyl)-N'-phenylurea, N-(o-toluenesulphonyl)-N'-phenylurea, N-(ptoluenesulphonyl)-N'-methylurea, N-(p-toluenesulphonyl)-N'-ethylurea, N,N'-bis(ptoluenesulphonyl)urea, N-benzylsulphonyl-N'-phenylurea, N-(2-phenoxyethane)sulphonyl-N'-phenylurea, N-(4-methoxybenzyl)sulphonyl-N'-phenylurea, N-(2-(p-chlorophenyl)ethane)sulphony]-N'-phenylurea, N-(p-biphenyl)sulphony]-N'-butylurea, N-benzylsulphonyl-N'-benzylurea, N-benzylsulphony]-N'-phenylthiourea, N-ethanesulphonyl-N'-1-naphthylurea, N-cyclohexanesulphonyl-N'-phenylurea, N-allylsulphonyl-N'-1-naphthylurea, N-(2-methoxyethanesulphonyl)-N'-biphenylurea, N-(2-tetrahydropyransulphonyl)-N'-1 naphthylurea, N-(2allyloxyethanesulphonyl)-N'-1-naphthylurea, N-isopropanesulphonyl-N'-benzylurea, N-isopropanesulphonyl-N'-(4-methylbenzyl)urea, N-methanesulphonyl-N'-(4-chloro-1naphthyl)urea, N-isopropanesulphonyl-N'-(4-chloro-l-naphthyl)urea, N-methanesulphonyl-N'-1-naphthyl-thiourea, N-(p-toluenesulphonyl)-N'-(p-methoxyphenyl)urea, N-(ptoluenesulphonyl)-N'-(m-hydroxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(phydroxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(p-ethoxycarbonylphenyl)urea, N-(ptoluenesulphonyl)-N'-(2-phenoxyethyl)urea, N-benzylsulphonyl-N'-(2-phenoxyethyl)urea, Nbenzylsulphonyl-N'-(p-methoxyphenyl)urea, N-(p-methoxybenzyl)sulphony]-N'-(2-(pchlorophenyloxy)ethyl)urea, N-methanesulphonyl-N'-(2-phenoxyethyl)urea, Nmethanesulphonyl-N'-(4-methoxy-1-naphthyl)urea, N-(p-toluenesulphonyl)-N'-(3-nbutylaminosulphonylphenyl)urea, N-(p-toluenesulphonyl)-N'-(4-trimethylacetophenyl)urea, N-(benzenesulphonyl)-N'-(3-p-toluenesulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-p-toluenesulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-phenylsulphonyl-

oxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(2-p-toluenesulphonyloxyphenyl )urea, N-(ptoluenesulphonyi)-N'-(2-phenyi- sulphonyioxyphenyi)urea, N-(p-toluenesulphonyi)-N'-(4benzoyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(4-phenylsulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(4-acetoxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(2-ptoluenesulphonyloxy-5-ethylsulphonyl phenyl)urea, N-(o-toluenesulphonyl)-N'-(3-ptoluenesulphonyloxyphenyl)urea, N-(4-chlorobenzenesulphonyl)-N'-(3-p-toluenesulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(4-p-toluenesulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-butylsulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(2methyl-4-p-toluenesulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(5-p-toluenesulphonyloxynapthyl)urea, N-(p-toluenesulphonyl)-N'-(4-p-tolyloxysulphonylphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-octylsulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-Hexadecylsulphonyloxyphenyl)urea, N-(octylsulphonyl)-N'-(3-p-toluenesulphonyloxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(4-phenylsulphonyloxyphenyl)urea, N-(phenylsulphonyl)-N'-(3-(p-toluenesulphonyloxy)phenyl)urea, N-(4-chlorophenylsulphonyl)-N'-(3-trimethylacetoxyphenyl)urea, N-(p-toluenesulphonyl)-N'-(4-(p-toluenesulphonyloxy)phenyl)urea, N-(p-toluenesulphonyl)-N'-(4-acetophenyl)urea, N-(p-toluenesulphonyl)-N'-(4acetamidosulphonylphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-(ethoxycarbonyloxy)phenyl)urea, N-(p-toluenesulphonyl)-N'-(3-(ethoxycarbamyl)phenyl)urea, N-(p-toluenesulphonyl)-N'-(3-(2-napthyl sulphonyloxy)phenyl)urea, N-(p-toluenesulphonyl)-N'-(4-benzoylphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-(4-toluenesulphonylamino)phenyl)urea, N-(ptoluenesulphonyl)-N'-(3-acetaminophenyl)urea, N-(4-chlorophenylsulphonyl)-N'-(4trimethylacetamidophenyl)urea, N-(benzenesulphonyl)-N'-(4-trimethylacetamidophenyl)urea, N-(4-chlorophenylsulphonyl)-N'-(2-(p-toluenesulphonyloxy)phenyl)urea, N-(p-toluenesulphonyl)-N'-(3-(N,N-di-p-toluenesulphonyl)aminophenyl)urea, N-(benzenesulphonyl)-N'-(2-(p-toluenesulphonyloxy)phenyl)urea, N-(4-chlorophenylsulphonyl)-N'-(4acetamidosulphonylphenyl)urea, N-(p-toluenesulphonyl)-N'-(3-(diphenylphosphinyl)phenyl)-

The multivalent group A of formula II is preferably selected from the group consisting of a] divalent carbonyl, thiocarbonyl and sulphonyl groups;

- b] multivalent aliphatic hydrocarbon groups;
- c] multivalent heteroatom containing aliphatic groups derived from aliphatic hydrocarbon compounds having at least one heteroatom located in a backbone chain per molecule thereof;

d] multivalent aliphatic groups derived from aliphatic hydrocarbon compounds having at least one member selected from the group consisting of carbonyl, thiocarbonyl, imide, imino and sulphonyl groups and ester structures located in a backbone chain per molecule thereof; e] multivalent aliphatic aromatic (aroaliphatic) groups derived from aliphatic hydrocarbon compounds having at least one member selected from the group consisting of unsubstituted and substituted aromatic hydrocarbon groups, located in a backbone chain per molecule thereof;

f] multivalent organic groups derived from aliphatic hydrocarbon compounds having at least one member selected from the group consisting of unsubstituted and substituted heterocyclic groups, located in a backbone chain per molecule thereof;

g] multivalent aromatic groups, derived from substituted and unsubstituted aromatic hydrocarbon compounds.

h] multivalent heterocyclic groups derived from unsubstituted and substituted heterocyclic compounds; and

i] multivalent organic groups derived from organic compounds in which two or more aromatic or heterocyclic groups are bonded to each other through one or more multivalent groups selected from the above mentioned groups a] to d].

Typical multivalent groups standing for A in formula II are as follows:

a]

b]

$$-CH_{2}CCH_{2} - CH_{2}COCH_{2}CH_{2}$$

$$-CH_{2}CH_{2} - CH_{2}CH_{2} - CH_{2}CH_{2}$$

$$-CH_{2}CH_{2} - CH_{2} - CH_{2} - CH_{2} - CH_{2}$$

$$g]$$

$$h]$$

$$i$$

wherein Y<sub>2</sub> is represented by -SO<sub>2</sub>-, -C(CH<sub>3</sub>)-, -CH<sub>2</sub>- or -O-

X is either an oxygen or sulphur atom, especially an oxygen atom and n is an integer 1, 2 or 3, preferably 1 or 2.

The stabilisers of formula II are exemplified by but not limited to: bis(p-methoxybenzenesulphonylaminocarbonylamino)ketone, 1,2-bis(p-methoxybenzenesulphonylaminocarbonylamino)ethane, 1,5-bis(p-methoxybenzenesulphonylaminocarbonylamino)-3-oxapentane, 1,3-bis(p-methoxybenzenesulphonylaminocarbonylamino)-2propane, 1,5-bis(p-methoxybenzenesulphonylaminocarbonylamino)-3-(2-(p-methoxybenzenesulfonylaminocarbonylamino)ethyl)-3-azapentane, 1,3-bis(p-methoxybenzenesulphonylaminocarbonylaminomethyl)benzene, 4,4'-bis(p-methoxybenzenesulphonylaminocarbonylamino) diphenylmethane, 4,4'-bis(p-methoxybenzenesulphonylaminothiocarbonylamino), diphenylmethane, 4,4'-bis(p-nitrobenzenesulphonylaminocarbonylamino) diphenylmethane, 4,4'-bis(m-trifluoromethylmethoxybenzenesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(p-phenoxybenzenesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(p-benzyloxybenzenesulphonyl aminocarbonylamino)diphenylmethane, 4,4'-bis(p-acetylbenzenesulphonyl aminocarbonylamino)diphenylmethane, 4,4'bis(p-benzoylbenzenesulphonyl aminocarbonylamino)diphenylmethane, 4,4'-bis(pallyloxybenzenesulphonyl aminocarbonylamino)diphenylmethane, 4,4'-bis(p-allylbenzenesulphonyl aminocarbonylamino)diphenylmethane, 4,4'-bis(p-ethyny-benzenesulphonyl aminocarbonylamino)diphenylmethane, 4,4'-bis(p-cyclohexylbenzene sulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(p-phenylbenzenesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(p-benzylbenzenesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(o-methoxybenzenesulphonylaminocarbonylamino) diphenylmethane, 4,4'-bis(p-ethoxybenzenesulphonylaminothiocarbonylamino)diphenylmethane, 2,2-bis(4'-(p-methoxybenzenesulphonylaminocarbonylamino)phenyl)propane, 1,2-bis(4'-(p-ethoxybenzenesulphonylaminocarbonylamino)phenyloxy)ethane, 3,3'-bis(p-methoxybenzenesulphonylaminocarbonylamino)diphenylsulphone, 4,4'-bis(p-methoxybenzenesulphonylaminocarbonylamino)diphenylether, 2,5-bis(p-methoxybenzenesulphonylaminocarbonylaminomethyl)furan; 1,3-bis(pmethoxybenzenesulphonylaminocarbonylamino)benzene, 1,5-bis(p-ethoxybonzenetoluenesulphonylaminocarbonylamino)naphthalene, bis(p-toluenesulphonylaminocarbonyamino)ketone, 1,2-bis(p-toluenesulphonylaminocarbonylamino)ethane, 1,1,6,6-tetra(p-toluenesulphonylaminocarbonylamino)heptane, 1,5-bis(p-toluenesulphonylaminocarbonylamino)-3-oxapentane, 1,5-bis(p-toluenesulphonylaminocarbonylamino)-3thiopentane, 1,3-bis(p-toluenesulphonylaminocarbonylamino)-2-propanone, 1,5-bis(ptoluenesulphonylaminocarbonylamino)3-[2'(p-toluenesulphonylaminocarbonyl-amino)ethyl]-

3-azapentane, 1,3-bis(p-toluenesulphonylaminocarbonylamino)methylbenzene, 1,4-bis(ptoluenesulphonylaminocarbonylamino)methylbenzene, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(o-toluenesulphonylaminocarbonylamino)}diphenylmethane, 4,4'-bis(benzenesulphonylamniocarbonylamino)-diphenylmethane, 4,4'-bis(l-naphthalenesulphonylaminocarbonylamino)-diphenylmethane, 2,2-bis[4'-(ptoluenesulphonylaminocarbonylamino)phenyl]propane, 1,2-bis[4'-(p-toluenesulphonylaminocarbonylamino)phenyloxy]ethane, 1,4-bis[3'-(p-toluenesulphonylaminocarbonylamino)phenyloxy]ethane, 2,5-bis(p-toluenesulphonylaminocarbonylamino)methylfuran. 1,3-bis(p-toluenesulphonylaminocarbonylamino)benzene, 1,4-bis(p-toluenesulphonylaminocarbonylamino)benzene, 1,5-bis(p-toluenesulphonylaminocarbonylamino)naphthalene. 1,8-bis(p-toluenesulphonylaminocarbonylamino)naphthalene, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)diphenylether, 3,3'-bis(p-toluenesulphonylaminocarbonylamino)diphenylsulphone, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)diphenylsulphone, 2,4-bis(p-toluenesulphonylaminocarbonylamino)toluene, 2,6-bis(p-toluenesulphonylaminocarbonylamino)toluene, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)diphenylsulphide, 3,4'-bis(p-toluenesulphonylaminocarbonylamino)diphenylether, 4,4-bis(methanesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(ethanesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(isopropanesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(trifluoromethanesulphonylaminocarbonylamino)diphenylmethane. 4,4'-bis(cyclohexanesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(allylsulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(2-methoxyethanesulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(2-tetrahydropyransulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(2-allyloxyethanesulphonylaminocarbonylamino)diphenylmethane, 1.5-bis(methanesulphonylaminocarbonylamino)naphthalene, 1,3-bis(methanesulphonylaminocarbonylamino)benzene, 4,4'-bis(methanesulphonylaminocarbonylamino)diphenylether, 4,4'-bis(methanesulphonylaminothiocarbonylamino) diphenylmethane, 4,4'-bis(benzylsulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(p-methylbenzylsulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(p-methoxybenzylsulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(p-chlorobenzylsulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(2-phenoxyethylsulphonylaminocarbonylamino)diphenylmethane, 4,4'-bis(2-(p-methoxyphenoxy)ethylsulphonylamino) diphenylmethane, 4,4'-bis(benzylsulphonylaminocarbonylamino) diphenylether, 1,5bis(benzylsulphonylaminocarbonylamino)naphthalene, 1,3-bis(benzylsulphonylamino-

ۇر. قۇرار carbonylamino)benzene, 4,4'-bis(benzylsulphonylaminothiocarbonylamino)diphenylmethane, 1,3-bis(p-toluenesulphonylaminocarbonylamino)-2-methylbenzene, 1,4-bis(p-toluenesulphonylaminocarbonylamino)-2,5-dimethylbenzene, 4,4'-bis(ptoluenesulphonylaminocarbonylamino)-3,3'-dimethyldiphenylmethane, 4,4'-bis(ptoluenesulphonylaminothiocarbonyl amino)-3,3'-dimethyldiphenylmethane, 4,4'-bis(otoluenesulphonylamino carbonylamino)-3,3'-dimethyldiphenylmethane, 4,4'-bis(benzenesulphonyl aminocarbonylamino)-3,3'-dimethyldiphenylmethane, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)-3,3'-diethyldiphenylmethane, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)-3,3'-dichloro diphenylmethane, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)-3,3',5,5'-tetramethyldiphenylmethane, 4,4'-bis(p-toluenesulphonylaminocarbonyl amino)-3,3',5,5'-tetraethyldiphenylmethane, 4,4'-bis(p-toluenesulphonyl aminocarbonylamino)-3,3'-dimethoxylbiphenyl, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)-3,3'-dimethylbiphenyl, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)-2,2',5,5'tetrachlorobiphenyl, 2,8-dimethyl-3,7-bis(p-toluenesulphonylaminocarbonylamino) dibenzothiophene-5,5-dioxide, 4,4'-bis(p-toluenesulphonylaminocarbonylamino)-3,3'dimethyldiphenylether, 2,5-bis(p-toluenesulphonylaminocarbonylaminomethyl)-3,5diethylfuran.

Y, can stand for the following preferred heterocyclic rings: thiazole, pyrazole, isoxazole, pyridine, pyrimidine, pyrazine, 1,2,4-triazine, indole, benzimidazole, benzothiazole, quinoline and benzoxazole.

The stabilisers of formula III are exemplified by but not limited to:

N-(p-toluenesulphonyl)-N'-(pyrid-3-yl)urea, N-(p-toluenesulphonyl)-N'-(6-methylpyridin-2-yl)urea, N-(p-toluenesulphonyl)-N'-(5-methylisoxazol-3-yl)urea, N-(p-toluenesulphonyl)-N'-(1,2-dihydro-1,5-dimethyl-2-phenyl-3H-pyrazyol-3-one)4-yl)urea, N-(p-toluenesulphonyl)-N'-(1.H.-indazol-6-yl)urea, N-(p-toluenesulphonyl)-N'-(4,6-dimethylpyrimidin-2-yl)urea, N-(p-toluenesulphonyl)-N'-(thiazol-2yl)urea, N-(p-toluenesulphonyl)-N'-(thiazol-2yl)urea, N-(p-toluenesulphonyl)-N'-(5-methyl-1.H.-pyrazol-3-yl)urea, N-(p-toluenesulphonyl)-N'-(benzimidazol-2-yl)urea, N-(p-toluenesulphonyl)-N'-(pyrimidin-2-yl)urea, N-(p-toluenesulphonyl)-N'-(4-(6-methylbenzothiazol-2yl)phenyl]urea, N-(p-toluenesulphonyl)-N'-(1.H.-[1,2,4]triazol-3-yl)urea.

All the exemplified stabilisers can be used singly or as a mixture with other stabilisers.

The stabilisers of formulae I, II and III are either known or can be prepared by the methods disclosed in WO 00/35679 and references therein.

The colour forming compounds are, for example, triphenylmethanes, lactones, benzoxazines, spiropyrans or preferably fluorans.

Preferred colour formers include but are not limited to; 3-diethylamino-6-methylfluoran, 3dimethylamino-6-methyl-7-anilinofluoran, 3-diethylamino-6-methyl-7-anilinofluoran, 3diethylamino-6-methyl-7-(2,4-dimethylanilino) fluoran, 3-diethylamino-6-methyl-7chlorofluoran, 3-diethylamino-6-methyl-7-(3-trifluoromethylanilino) fluoran, 3-diethylamino-6-methyl-7-(2-chloroanilino) fluoran, 3-diethylamino-6-methyl-7-(4-chloroanilino) fluoran, 3diethylamino-6-methyl-7-(2-fluoroanilino) fluoran, 3-diethylamino-6-methyl-7-(4-noctylanilino) fluoran, 3-diethylamino -7-(4-n-octylanilino) fluoran, 3-diethylamino -7-(noctylamino) fluoran, 3-diethylamino -7-(dibenzylamino) fluoran, 3-diethylamino-6-methyl-7-(dibenzylamino) fluoran, 3-diethylamino-6-chloro-7-methylfluoran, 3-diethylamino-7-tbutylfluoran, 3-diethylamino -7-carboxyethylfluoran, 3-diethylamino-6-chloro-7anilinofluoran, 3-diethylamino-6-methyl-7-(3-methylanilino) fluoran, 3-diethylamino-6methyl-7-(4-methylanilino) fluoran, 3-diethylamino-6-ethoxyethyl-7-anilinofluoran, 3diethylamino-7-methylfluoran, 3-diethylamino-7-chlorofluoran, 3-diethylamino-7-(3trifluoromethylanilino) fluoran, 3-diethylamino-7-(2-chloroanilino) fluoran, 3-diethylamino-7-(2-fluoroanilino) fluoran, 3-diethylamino-benzo[a] fluoran, 3-diethylamino-benzo[c] fluoran, 3-dibutylamino-7-dibenzylaminofluoran, 3-dibutylamino-7-anilinofluoran, 3-diethylamino-7-anilinofluoran, 3-dibutylamino-6-methyl fluoran, 3-dibutylamino-6-methyl-7anilinofluoran, 3-dibutylamino-6-methyl-7-(2,4-dimethylanilino) fluoran, 3-dibutylamino-6methyl-7-(2-chloroanilino) fluoran, 3-dibutylamino-6-methyl-7-(4-chloroanilino) fluoran, 3dibutylamino-6-methyl-7-(2-fluoroanilino) fluoran, 3-dibutylamino-6-methyl-7-(3trifluoromethylanilino) fluoran, 3-dibutylamino-6-ethoxyethyl-7-anilinofluoran, 3dibutylamino-6-chloro-anilinofluoran, 3-dibutylamino-6-methyl-7-(4-methylanilino) fluoran, 3-dibutylamino-7-(2-chloroanilino) fluoran, 3-dibutylamino-7-(2-fluoroanilino) fluoran, 3dipentylamino-6-methyl-7-anilinofluoran, 3-dipentylamino-6-methyl-7-(2-chloroanilino) fluoran, 3-dipentylamino-6-methyl-7-(4-chloroanilino) fluoran 3-dipentylamino-7-(3trifluoromethylanilino) fluoran, 3-dipentylamino-6-chloro-7-anilinofluoran, 3-dipentylamino-7-(4-chloroanilino) fluoran, 3-pyrrolidino-6-methyl-7-anilinofluoran, 3-piperidino-6-methyl-7-

anilinofluoran, 3-(N-methyl-N-propylamino)-6-methyl-7-anilinofluoran, 3-(N-methyl-Ncyclohexylamino)-6-methyl-7-anilinofluoran, 3-(N-ethyl-N-cyclohexylamino)-6-methyl-7anilinofluoran, 3-(N-ethyl-p-toluidino)-6-methyl-7-anilinofluoran, 3-(N-ethyl-Nisoamylamino)-6-methyl-7-anilinofluoran, 3-(N-ethyl-N-isoamylamino)-6-chloro-7anilinofluoran, 3-(N-ethyl-N-tetrahydrofurfurylamino)-6-methyl-7-anilinofluoran, 3-(N-ethyl-N-isobutylamino)-6-methyl-7-anilinofluoran, 3-(N-butyl-N-isoamylamino)-6-methyl-7anilinofluoran, 3-(N-isopropyl-N-3-pentylamino)-6-methyl-7-anilinofluoran, 3-(N-ethyl-Nethoxypropylamino)-6-methyl-7-anilinofluoran, 3-cyclohexylamino-6-chlorofluoran, 2methyl-6-p-(p-dimethylaminophenyl)aminoanilinofluoran, 2-methoxy-6-p-(pdimethylaminophenyl)aminoanilinofluoran, 2-chloro-3-methyl-6-p-(pphenylaminophenyl)aminoanilinofluoran, 2-diethylamino-6-p-(pdimethylaminophenyl)aminoanilinofluoran, 2-phenyl-6-methyl--6-p-(pphenylaminophenyl)aminoanilinofluoran, 2-benzyl-6-p-(pphenylaminophenyl)aminoanilinofluoran, 3-methyl-6-p-(pdimethylaminophenyl)aminoanilinofluoran, 3-diethylamino-6-p-(pdiethylaminophenyl)aminoanilinofluoran, 3-diethylamino-6-p-(pdibutylaminophenyl)aminoanilinofluoran, 2,4-dimethyl-6-[(4-dimethylamino)anilino] fluoran, 3-[(4-dimethylaminophenyl)amino]-5,7-dimethylfluoran, 3,6,6'tris(dimethylamino)spiro[fluorene-9,3'-phthalide], 3,6,6'-tris(diethylamino)spiro[fluorene-9,3'-phthalide], 3,3-bis(p-dimethylaminophenyl)-6-dimethylaminophthalide, 3,3-bis(pdimethylaminophenyl)phthalide, 3,3-bis-[2-(p-dimethylaminophenyl)-2-(pmethoxyphenyl)ethenyl-4,5,6,7-tetrabromophthalide, 3,3-bis-[2-(p-dimethylaminophenyl)-2-(p-methoxyphenyl)ethenyl-4,5,6,7tetrachlorophthalide, 3,3-bis[1,1-bis(4-pyrrolidinophenyl)ethylene-2-yl]-4,5,6,7tetrabromophthalide, 3,3-bis-[1-(4-methoxyphenyl)-1-(4-pyrridinophenyl)ethylene-2-yl]-4,5,6,7-tetrachlorophthalide, 3-(4-diethylamino-2-ethoxyphenyl)-3-(1-ethyl-2-methylindole-3-yl)-4-azaphthalide, 3-(4-diethylamino-2-ethoxyphenyl)-3-(1-octyl-2-methylindole-3-yl)-4azaphthalide, 3-(4-cyclohexylethylamino-2-methoxyphenyl)-3-(1-ethyl-2-methylindole-3-yl)-4-azaphthalide, 3,3-bis(1-ethyl-2-methylindole-3-yl) phthalide, 3,3-bis(1-octyl-2methylindole-3-yl) phthalide, mixture of 2-phenyl-4-(4-diethylaminophenyl)-4-(4methoxyphenyl)-6-methyl-7-dimethylamino-3,1-benzoxazine and 2-phenyl-4-(4diethylaminophenyl)-4-(4-methoxyphenyl)-8-methyl-7-dimethylamino-3,1-benzoxazine, 4,4'-[1-methylethylidene)bis(4,1-phenyleneoxy-4,2-quinazolinediyl)]bis[N,N-

diethylbenzenamine], bis(N-methyldiphenylamine)-4-yl-(N-butylcarbazole)-3-yl-methane and mixtures thereof.

All of the above colour forming compounds can be used singly or as a mixture with other colour forming compounds; or they may also be used together with further black colour forming compounds.

Highly preferred are 3-diethylamino-6-methyl-7-anilinofluoran, 3-diethylamino-6-methyl-7-(3-methylanilino) fluoran, 3-diethylamino-6-methyl-7-(2,4-dimethylanilino) fluoran, 3-dibutylamino-6-methyl-7-anilinofluoran, 3-dipentylamino-6-methyl-7-anilinofluoran, 3-(N-methyl-N-propylamino)-6-methyl-7-anilinofluoran, 3-(N-methyl-7-anilinofluoran, 3-(N-methyl-7-anilinofluoran, 3-diethylamino-6-chloro-7-anilinofluoran, 3-dibutylamino-7-(2-chloroanilino)fluoran, 3-(N-ethyl-N-p-toluidino)-6-methyl-7-anilinofluoran, 3-(N-ethyl-N-tetrahydrofurfurylamino)-6-methyl-7-anilinofluoran, 3-(N-ethyl-N-anilinofluoran, 3-(N-ethyl-N-anilinofluoran, 3-N-ethyl-N-ethoxypropylamino-6-methyl-7-anilinofluoran, 2,4-dimethyl-6-[(4-dimethylamino)anilino]fluoran and mixtures thereof.

It is also possible to use solid solutions comprising at least two colour forming compounds as described in PCT Patent Application 00/12318.

The monophase solid solutions can be used singly or as a mixture with other colour forming compounds such as triphenylmethanes, lactones, fluorans, benzoxazines and spiropyrans; or they may also be used together with further black colour forming compounds. Examples of such other colour forming compounds are given hereinbefore.

In addition, the inventive composition contains a developer (component b), which is different from the sensitizer used as component c). Such developers are exemplified by, but not limited to: 4,4'-isopropylidene bisphenol, 4,4'-sec-butylidene bisphenol, 4,4'-cyclohexylidene bisphenol, 2,2-bis-(4-hydroxyphenyl)-4-methylpentane, 2,2-dimethyl-3,3-di(4-hydroxyphenyl)butane, 2,2'-dihydroxydiphenyl, 1-phenyl-1,1-bis(4-hydroxyphenyl)butane, 4-phenyl-2,2-bis(4-hydroxyphenyl)butane, 1-phenyl-2,2-bis(4-hydroxyphenyl)butane, 2,2-bis(4'-hydroxy-3'-methylphenyl)-4-methylpentane, 2,2-bis(4'-hydroxy-3'-methylphenyl)-4-methylphenyl

hydroxy-3'-tert-butylphenyl)-4-methylpentane, 4,4'-sec-butylidene-bis (2-methylphenol), 4,4'-isopropylidene-bis (2-tert-butylphenol), 2,2-bis(4'-hydroxy-3'-isopropylphenyl)-4methylpentane, allyl-4,4-bis (4'-hydroxyphenyl) pentanoate, propargyl-4,4-bis(4'hydroxyphenyl) pentanoate, n-propyl-4,4-bis (4'-hydroxyphenyl) pentanoate, 2,4-bis (phenylsulfonyl) phenol, 2-(4-methylsulfonyl)-4-(phenylsulfonyl) phenol, 2-(phenylsulfonyl)-4-(4-methylsulfonyl) phenol, 2,4-bis (4-methylphenylsulfonyl) phenol, pentamethylene-bis(4hydroxybenzoate), 2,2-dimethyl-3,3-di(4-hydroxyphenyl)pentane, 2,2-di(4hydroxyphenyl)hexane, 4,4'-dihydroxydiphenyl thioether, 1,7-di(4-hydroxyphenylthio)-3,5dioxaheptane, 2,2'-bis(4-hydroxyphenylthio)diethyl ether, 4,4'-dihydroxy-3,3'dimethylphenyl thioether; benzyl-4-hydroxybenzoate, ethyl-4-hydroxybenzoate, propyl-4hydroxybenzoate, isopropyl-4-hydroxybenzoate, butyl-4-hydroxybenzoate, isobutyl-4hydroxybenzoate, 4,4'-dihydroxydiphenyl sulfone, 2,4'-dihydroxydiphenyl sulfone, 4hydroxy-4'-methyldiphenyl sulfone, 4-hydroxy-4'-isopropoxydiphenyl sulfone, 4-hydroxy-4'butoxydiphenyl sulfone, 4,4'-dihydroxy-3,3'-diallyldiphenyl sulfone, 3,4-dihydroxy-4'methyldiphenyl sulfone, 4,4'-dihydroxy-3,3',5,5'-tetrabromodiphenyl sulfone, 4,4'-bis (ptoluenesulphonylaminocarbonylamino) diphenylmethane, N-p-toluenesulphonyl-N'-phenyl urea, N-p-toluenesulphonyl-N'-[3-O-p-toluenesulphonyl]phenyl urea, dimethyl 4hydroxyphthalate, dicyclohexyl 4-hydroxyphthalate, diphenyl 4-hydroxyphthalate, 4-[2-(4methoxyphenyloxy)ethyloxy] salicylate, 3,5-di-tert-butylsalicylic acid, 3-benzyl salicylic acid, 3-( $\alpha$ -methylbenzyl) salicylic acid, 3-phenyl-5-( $\alpha$ ,  $\alpha$ -dimethylbenzyl) salicylic acid, 3,5-di- $\alpha$ methylbenzyl salicylic acid; metal salts of salicylic acid, 2-benzylsulfonylbenzoic acid, 3cyclohexyl-4-hydroxybenzoic acid, zinc benzoate, zinc 4-nitrobenzoate, 4-(4'phenoxybutoxy)phthalic acid, 4-(2'-phenoxyethoxy)phthalic acid, 4-(3'phenylpropyloxy)phthalic acid, mono (2-hydroxyethyl) -5-nitro-isophthalic acid, 5benzyloxycarbonyl isophthalic acid, 5-(1'-phenylethanesulfonyl) isophthalic acid, bis(1,2dihydro-1,5-dimethyl-2-phenyl-3H-pyrazol-3-one-O)bis(thiocyanato-N) zinc and mixtures thereof.

In a preferred embodiment, the inventive composition can contain a sensitiser. The weight ratio of sensitiser:colour former usually is chosen in the range from 0.5:1 to 3.0:1, preferably 1:1 to 2:1.

Representative examples of sensitiser are stearamide, methylol stearamide, p-benzylbiphenyl, m-terphenyl, 2-benzyloxynaphthalene, 4-methoxybiphenyl, dibenzyl oxalate, di(4-

methylbenzyl) oxalate, di(4-chlorobenzyl) oxalate, dimethyl phthalate, dibenzyl terephthalate, dibenzyl isophthalate, 1,2-diphenoxyethane, 1,2-bis(4-methylphenoxy) ethane, 1,2-bis(3-methylphenoxy) ethane, 4,4'-dimethylbiphenyl, phenyl-1-hydroxy-2-naphthoate, 4-methylphenyl biphenyl ether, 1,2-bis(3,4-dimethylphenyl) ethane, 1,4-diethoxynaphthalene, 1,4-diacetoxybenzene, 1,4-diproprionoxybenzene, o-xylylene-bis(phenyl ether), 4-(m-methylphenoxymethyl) biphenyl, p-hydroxyacetanilide, p-hydroxybutyranilide, p-hydroxynonananilide, p-hydroxylauranilide, p-hydroxyoctadecananilide.

The above sensitisers are known or can be prepared according to known methods.

Another embodiment relates to a heat sensitive recording material which comprises a sheet substrate and a heat sensitive coloured image-forming layer formed on the surface of the supporting substrate, comprising the inventive composition, a binder and if needed other additives.

Usually the binder is added in an effective amount. As a rule the weight ratio of binder:colour former is chosen in the range of from as 0.5:1 to 4:1, preferably 3.5:1.

Representative binders used for the heat sensitive recording material include polyvinyl alcohol (fully and partially hydrolysed), carboxy, amide, sulfonic and butyral modified polyvinyl alcohols, derivatives of cellulose such as hydroxyethyl cellulose, methyl cellulose, ethyl cellulose, carboxymethyl cellulose and acetyl cellulose, copolymer of styrene-maleic anhydride, copolymer of styrene-butadiene, polyvinyl chloride, polyvinyl acetate, polyacrylamide, polyamide resin and mixtures thereof.

Exemplary fillers, which can be used include calcium carbonate, kaolin, calcined kaolin, aluminium hydroxide, talc, titanium dioxide, zinc oxide, silica, polystyrene resin, ureaformaldehyde resin, hollow plastic pigment and mixtures thereof.

Representative lubricants for use in heat sensitive recording materials include stearamide, methylene bisstearamide, polyethylene, carnauba wax, paraffin wax, zinc stearate or calcium stearate and mixtures thereof.

Other additives can also be employed, if necessary. Such additives are for example fluorescent whitening agents and ultraviolet absorbers. The ultraviolet absorbers may be employed in either the thermosensitive colouring layer or in a protective layer, and if desired, may be used in microencapsulated form in the protective layer.

Representative examples of ultraviolet absorbers that may be used in the invention include phenyl salicylate, p-tert-butylphenyl salicylate, p-octylphenyl salicylate and like salicylic acid type ultraviolet absorbers:

2,4-Dihydroxybenzophenone, 2-hydroxy-4-methoxybenzophenone, 2-hydroxy-4-octyloxybenzophenone, 2-hydroxy-4-dodecyloxybenzophenone, 2,2'-dihydroxy-4-methoxybenzophenone, 2,2'-dihydroxy-4,4'-dimethoxybenzophenone, 2-hydroxy-4-methoxy-5-sulfobenzophenone and like benzophenone type ultraviolet absorbers; 2-Ethylhexyl-2-cyano-3,3-diphenylacrylate, ethyl-2-cyano-3,3-diphenylacrylate and like cyanoacrylate type ultraviolet absorbers; Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate, bis(2,2,6,6-tetramethyl-4-piperidyl) succinate, bis(1,2,2,6,6-pentamethyl-4-piperidyl)-2-(3,5-di-tert-butyl-4-hydroxybenzyl)-2-n-butyl malonate and like hindered amine type ultraviolet absorbers;

2-(2'-Hydroxyphenyl) benzotriazole, 2-(2'-hydroxy-5'-methylphenyl) benzotriazole, 2-(2'-hydroxy-5'-tert-butylphenyl) benzotriazole, 2-(2'-hydroxy-3,5'-di-tert-butylphenyl) benzotriazole, 2-(2'-hydroxy-3,5'-di-tert-butylphenyl)-5-chlorobenzotriazole, 2-(2'-hydroxy-3,5'-di-tert-butylphenyl)-5-chlorobenzotriazole, 2-(2'-hydroxy-3,5'-di-tert-butylphenyl)-5-tert-butylphenyl)-5-tert-butylphenyl)-5-tert-butylphenyl)-5-tert-amylphenyl)-5-tert-amylphenyl)-5-methoxybenzotriazole, 2-(2'-hydroxy-3,5'-di-tert-amylphenyl)-5-methoxybenzotriazole, 2-(2'-hydroxy-3'-(3",4",5",6"-tetrahydrophthalimidomethyl)-5'-methylphenyl] benzotriazole, 2-(2'-hydroxy-5'-tert-octylphenyl)benzotriazole, 2-(2'-hydroxy-3'-sec-butyl-5'-tert-butylphenyl) benzotriazole, 2-(2'-hydroxy-3'-tert-amyl-5'-phenoxyphenyl)-5-methylbenzotriazole, 2-(2'-hydroxy-5'-n-dodecylphenyl) benzotriazole, 2-(2'-hydroxy-5'-sec-octyloxyphenyl)-5-phenylbenzotriazole, 2-(2'-hydroxy-3'-tert-amyl-5'-phenylphenyl)-5-methoxybenzotriazole, 2-[2'-hydroxy-3',5'-bis(α,α-dimethylbenzyl)-phenyl] benzotriazole and like benzotriazole ultraviolet absorbers;

2-(2'-Hydroxy-3'-dodecyl-5'-methylphenyl) benzotriazole, 2-(2'-hydroxy-3'-undecyl-5'methylphenyl) benzotriazole, 2-(2'-hydroxy-3'-tridecyl-5'-methylphenyl) benzotriazole, 2-(2'-hydroxy-3'-tetradecyl-5'-methylphenyl) benzotriazole, 2-(2'-hydroxy-3'-pentadecyl-5'methylphenyl) benzotriazole, 2-(2'-hydroxy-3'-hexaadecyl-5'-methylphenyl) benzotriazole, 2-[2'-hydroxy-4'-(2"-ethylhexyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(2"ethylheptyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(2"-ethyloctyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(2"-propyloctyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(2"-propylheptyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(2"-propylhexyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(1"-ethylhexyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(1"-ethylheptyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(1"-ethyloctyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(1"-propyloctyl)oxyphenyl] benzotriazole, 2-[2'-hydroxy-4'-(1"-propylheptyl)oxyphenyl] benzotriazole, , 2-[2'-hydroxy-4'-(1"-propylhexyl)oxyphenyl] benzotriazole, 2-(2'-hydroxy-3'-sec-butyl-5'-tert-butylphenyl)-5-n-butylbenzotriazole, 2-(2'hydroxy-3'-sec-butyl-5'-tert-butylphenyl)-5'-tert-pentylbenzotriazole, 2-(2'-hydroxy-3'-secbutyl-5'-tert-butylphenyl)-5-n-pentylbenzotriazole, 2-(2'-hydroxy-3'-sec-butyl-5'-tertpentylphenyl)-5'-tert-butylbenzotriazole, 2-(2'-hydroxy-3'-sec-butyl-5'-tert-pentylphenyl)-5'n-butylbenzotriazole, 2-(2'-hydroxy-3',5'-di-tert-butylphenyl)-5-sec-butylbenzotriazole, 2-(2'hydroxy-3',5'-di-tert-pentylphenyl)-5-sec-butylbenzotriazole, 2-(2'-hydroxy-3'-tert-butyl-5'tert-pentylphenyl)-5-sec-butylbenzotriazole, 2-(2'-hydroxy-3,5'-di-sec-butylphenyl)-5chlorobenzotriazole, 2-(2'-hydroxy-3,5'-di-sec-butylphenyl)-5-methoxybenzotriazole, 2-(2'hydroxy-3,5'-di-sec-butylphenyl)-5-tert-butylbenzotriazole, 2-(2'-hydroxy-3,5'-di-secbutylphenyl)-5-n-butylbenzotriazole, octyl-5-tert-butyl-3-(5-chloro-2H-benzotriazole-2-yl)-4hydroxybenzene propionate, condensate of methyl -3-[tert-butyl-5-(2H-benzotriazole-2-yl)-4-hydroxyphenyl] propionate and polyethylene glycol (molecular weight: about 300) and like benzotriazole ultraviolet absorbers.

The heat sensitive recording material of the invention can be prepared according to conventional methods. For example, at least one colour forming compound, at least one developer, at least one sensitiser are ground separately in water or a suitable dispersing medium, such as aqueous polyvinyl alcohol, to form an aqueous or other dispersion. A compound of formula I, II or III is treated in the same manner. The fine particle dispersions thus obtained are combined and then mixed with conventional amounts of binder, filler and lubricant.

The coating liquid so obtained can be applied to a suitable substrate such as paper, plastic sheet and resin coated paper, and used as the heat sensitive recording material. The system of the invention can be employed for other end use applications using colour forming materials, for example, a temperature indicating material.

The quantity of the coating is usually in the range of 2 to 10 g/m<sup>2</sup>, most often in the range 4 to 8 g/m<sup>2</sup>.

The recording material containing such a thermosensitive colouring layer can in addition contain a protective layer and, if desired, an undercoat layer. The undercoat layer may be interposed between the substrate and the thermosensitive colouring layer.

The protective layer usually comprises a water-soluble resin in order to protect the thermosensitive colouring layer. If desired, the protective layer may contain water-soluble resins in combination with water-insoluble resins.

As such resins conventional resins can be employed. Specific examples are: polyvinyl alcohol; starch and starch derivatives; cellulose derivatives such as methoxycellulose, hydroxyethylcellulose, carboxymethylcellulose, methylcellulose and ethylcellulose; sodium polyacrylate; polyvinyl pyrrolidone; polyacrylamide/acrylic acid ester copolymers; acrylamide/acrylic acid ester/methacrylic acid copolymers; alkali metal salts of styrene/maleic anhydride copolymers; alkali metal salts of isobutylene/maleic anhydride copolymers; polyacrylamide; sodium alginate; gelatin; casein; water-soluble polyesters and carboxyl-group-modified polyvinyl alcohols.

The protective layer may also contain a water-resisting agent such as a polyamide resin, polyamido-epichlorhydrin resin, melamine-formaldehyde resin, formaldehyde, glyoxal or chromium alum.

Furthermore, the protective layer may contain fillers, such as finely-divided inorganic powders, e.g. of calcium carbonate, silica, zinc oxide, titanium oxide, aluminium hydroxide, zinc hydroxide, barium sulphate, clay, talc, surface-treated calcium or silica, or a finely-divided organic powder of, e.g., a urea-formaldehyde resin, a styrene/methacrylic acid copolymer or polystyrene.

The undercoat layer usually contains as its main components a binder resin and a filler. Specific examples of binder resins for use in the undercoat layer are: polyvinyl alcohol; starch and starch derivatives; cellulose derivatives such as methoxycellulose, hydroxyethylcellulose, carboxymethylcellulose, methylcellulose and ethylcellulose; sodium polyacrylate; polyvinyl pyrrolidone; polyacrylamide/acrylic acid ester copolymers; acrylamide/acrylic acid ester/methacrylic acid copolymers; alkali metal salts of styrene/maleic anhydride copolymers; alkali metal salts of isobutylene/maleic anhydride copolymers; polyacrylamide; sodium alginate; gelatin; casein; water-soluble polymers such as water-soluble polyesters and carboxyl-group-modified polyvinyl alcohols; polyvinyl acetate; polyurethanes; styrene/butadiene copolymers; polyacrylic acid; polyacrylic acid esters; vinyl chloride/vinyl acetate copolymers; polybutylmethacrylate; ethylene/vinylacetate copolymers and styrene/butadiene acrylic derivative copolymers.

Specific examples of fillers for use in the undercoat layer are: finely-divided inorganic powders, e.g. of calcium carbonate, silica, zinc oxide, titanium oxide, aluminium hydroxide, zinc hydroxide, barium sulphate, clay, talc, surface-treated calcium, silica or calcined clay (e.g. Ansilex, Engelhard Corp.), and finely-divided organic powders of, e.g., urea-formaldehyde resins, styrene/methacrylic acid copolymers and polystyrene.

In addition, the undercoat layer may contain a water-resisting agent. Examples of such agents are given above.

In particular the invention provides exceptional resistance to plasticiser, oil and heat ageing whilst showing improved background whiteness.

#### <u>Examples</u>

Preparation of heat sensitive coating formulations containing a stabiliser as defined herein:

Dispersions A to D are prepared by grinding the compositions shown below in an attritor until an average particle size of 1 to 1.5  $\mu$  is attained.

Dispersion A (Colour Former)			
3-dibutylamino-6-methyl-7-anilinofluoran	3.01 parts		
Polyvinyl alcohol (10% aqueous solution)	10.50 parts		
	6.49 parts		
Water	•		
7 (5 Lun Developes)			
Dispersion B (Colour Developer)	7.50 parts		
Colour developer	•		
Polyvinyl alcohol (10% aqueous solution)	7.50 parts		
Water	22.50 parts		
Dispersion C (Sensitiser)			
Sensitiser	10.00 parts		
	10.00 parts		
Polyvinyl alcohol (10% aqueous solution)	20.00 parts		
Water	20,00 pm a		
Dispersion D (Stabiliser)			
Stabiliser	7.50 parts		
Polyvinyl alcohol (10% aqueous solution)	7.50 parts		
Water	22.50 parts		
yyaccı			

A thermal coating mixture is then prepared by combining together the following components:

	parts by weight
Dispersion A	6.6
Dispersion B	12.5
Dispersion C	6.0
Dispersion D	2.5
Calcium Carbonate (25% aqueous dispersion)	13.2
Zinc stearate (33% aqueous dispersion)	1.5
Polyvinyl alcohol (10% aqueous solution)	6.5
Tinopal® ABP-X (fluorescent whitening agent)	0.12
Water	2.58

This coating mixture is applied on one side of a base paper weighing 50 g/m<sup>2</sup> in a coating weight of about 5.0 g/m<sup>2</sup> and then dried. The resulting sheet is calandered by means of a laboratory calander to produce a recording sheet with excellent background whiteness.

#### **DESCRIPTION OF TEST METHODS:**

#### Lightfastness Tests (120 Hours Exposure):

This test assesses the stability of the imaged and un-imaged thermal paper to sunlight.

An image is produced using an Atlantek thermal response tester model 200. The image including background is placed at a distance of 8cm below 40W fluorescent tubes emitting artificial sunlight (approximately 1200 Lux) for 120 hours. The optical density of the image and background whiteness of the paper are measured before and after exposure with a Macbeth 1200 series Densitometer.

#### Cottonseed Oil Resistance of Image:

This test assesses the stability of the image when exposed to cottonseed oil.

An image is produced using an Atlantek thermal response tester model 200. Cottonseed oil is then gravure printed onto the image, which is then stored at 40°C for 24 hours. The optical density of the image is measured using a Macbeth 1200 series Densitometer before and after exposure.

#### Plasticiser Resistance of Image and Background:

This test assesses the stability of the image and background when exposed to PVC containing 20-25% phthalate ester-type plasticiser.

An image is produced using an Atlantek thermal response tester model 200. The image is put into contact with the PVC under 107g cm<sup>-2</sup> pressure for 24 hours at 50°C. The optical density of the image and background are measured using a Macbeth 1200 series Densitometer before and after exposure.

#### Waterfastness of Image:

This test assesses the stability of the image after immersion in water.

An image is produced using an Atlantek thermal response tester model 200. The image is immersed in de-ionised water at room temperature for 3 hours. The optical density of the image is measured using a Macbeth 1200 series Densitometer before and after immersion.

#### Heat and Moisture Resistance of Image:

This test assesses the effects of heat and moisture on the image.

An image is produced using an Atlantek thermal response tester model 200. The image is aged at 60°C at 70% R.H. for 24 hours. The optical density of the image is measured using a Macbeth 1200 series Densitometer before and after exposure.

<u>Example 1</u>: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-O-p-toluenesulphonyl]phenyl urea as stabiliser (Dispersion D) with 2,4'-dihydroxydi-phenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

The heat sensitive recording paper obtained demonstrates good background whiteness of the paper after application of the coating liquid and also after carrying out storage stability i.e. resistance to light, heat and moisture, of the uncoloured portion of the coated paper. Image stability is excellent and the performance against thermal paper coated without a stabiliser is summarised in Table 1. Additionally the recording paper obtained shows a high dynamic sensitivity.

<u>Example 2</u>: A coating mixture was prepared as described in Example 1, but the quantity of stabiliser is reduced by 50%.

<u>Example 3</u>: A coating mixture is prepared as described in Example 1, but the quantity of stabiliser is reduced by 80%.

<u>Example 4</u>: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-O-p-toluenesulphonyl]phenyl urea as stabiliser (Dispersion D) with 2,2-bis-(4hydroxyphenyl)-4-methylpentane as developer (Dispersion B) and p-benzylbiphenyl as sensitiser (Dispersion C).

<u>Example 5</u>: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-O-p-toluenesulphonyl]phenyl urea as stabiliser (Dispersion D) with 2,2-bis-(4hydroxyphenyl)-4-methylpentane as developer (Dispersion B) and 1,2-diphenoxyethane as sensitiser (Dispersion C).

Example 6: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-O-p-toluenesulphonyl]phenyl urea as stabiliser (Dispersion D) with a mixture of 3-dibutylamino-6-methyl-7-anilinofluoran and 3-diethylamino-6-methyl-7-anilinofluoran in the ratio of 30:70 as colour former (Dispersion A), 2,2-bis-(4hydroxyphenyl)-4-methylpentane as developer (Dispersion B) and p-benzylbiphenyl as sensitiser (Dispersion C).

Example 7: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-O-p-toluenesulphonyl]phenyl urea as stabiliser (Dispersion D) with a mixture of 3-dibutylamino-6-methyl-7-anilinofluoran and 3-diethylamino-6-methyl-7-anilinofluoran in the ratio of 30:70 as colour former (Dispersion A), 2,2-bis-(4hydroxyphenyl)-4-methylpentane as developer (Dispersion B) and 1,2-diphenoxyethane as sensitiser (Dispersion C).

<u>Example 8</u>: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-carboxyphenyl]urea as stabiliser (Dispersion D) with bisphenol A as developer (Dispersion B) and p-benzylbiphenyl as sensitiser (Dispersion C).

<u>Example 9</u>: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-carboxy-phenyl]urea as stabiliser (Dispersion D) with 4-hydroxy-4'-isopropoxy-diphenylsulphone as developer (Dispersion B) and p-benzylbiphenyl as sensitiser (Dispersion C).

Example 10: A coating mixture is prepared using N-p-toluenesulphonyl-N'-[3-carboxy-phenyl]urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Table 1

Example	Initial	Lightfastness	Heat and	Plasticiser	Cottonseed Oil	Water
	Image		Moisture	resistance	resistance	Fastness
	Density		Resistance			
1	+	0	++	++	++	0
2	+	0	+	++	++	0
3	+	0	0	++	+-+	0
4	0	0	+	++	++	0
5	0	0	++	++	+-1-	0
6	0	0	0	++	++	0
7	0	0	0	+	+	0
8	0	0	+	+	++	++
9	0	+	+	+	++	++
10	0	+	+	+	++	+

Key:

- O Similar performance when compared to against thermal paper coated without a stabiliser.
- + Improved performance when compared to against thermal paper coated without a stabiliser.
- ++ Superior performance when compared to against thermal paper coated without a stabiliser.

Example 11: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(pyrid-3-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

The heat sensitive recording paper obtained demonstrates good background whiteness of the paper after application of the coating liquid and also after carrying out storage stability i.e. resistance to light, heat and moisture, of the uncoloured portion of the coated paper. Image stability is excellent and the performance against thermal paper coated without a stabiliser is summarised in Table 2. Additionally the recording paper obtained shows a high dynamic sensitivity.

<u>Example 12</u>: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(6-methylpyidin-2-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 13: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(5-methylisoxazol-3-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 14: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-((1,2-dihydro-1,5-dimethyl-2-phenyl-3H-pyrazol-3-one)4-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 15: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(1.H.-indazol-6-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 16: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(4,6-dimethylpyrimidin-2-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 17: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(benzothiazol-2-yl)urea as stabiliser (Dispersion D) at a reduced level of 50% with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 18: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(thiazol-2yl)urea as stabiliser (Dispersion D) at a reduced level of 50% with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 19: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(5-methyl-1.H.-pyrazol-3-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 20: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(benzimidazol-2-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 21: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(pyrimidin-2-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

<u>Example 22</u>: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(6-methane-sulphonylbenzothiazol-2-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenyl-sulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 23: A coating mixture is prepared using, N-(p-toluenesulphonyl)-N'-[4-(6-methylbenzothiazol-2yl)phenyl]urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Example 24: A coating mixture is prepared using N-(p-toluenesulphonyl)-N'-(1H-[1,2,4]triazol-3-yl)urea as stabiliser (Dispersion D) with 2,4'-dihydroxydiphenylsulphone as developer (Dispersion B) and di-(p-methylbenzyl)oxalate as sensitiser (Dispersion C).

Table 2

Example	Initial	Lightfastness	Heat and	Plasticiser	Cottonseed	Water
	Image		Moisture	resistance	Oil	Fastness
	Density		Resistance		resistance	
11	0	0	+	+	+	0
12	0	0	++	++	++	0
13	0	0	+	+	++	0
14	0	0	+	+	++	0
15	0	0	++	+	++	0
16	0	0	+	+	+	0
17	0	0	++	+	++	0
18	0	0	++	+	+	0
19	0	0	++	++	++	۱ 0
20	0	0	++	+	+	0 :
21	0	0	++	++	0	0
22	0	0	++	++	+	0
23	0	0	++	++	++	0 .
24	0	0	++	+	0	0 .
Key:	0 Si	imilar performance	when compar	red to against t	hermal	

- Similar performance when compared to against thermal paper coated without a stabiliser.
- Improved performance when compared to against + thermal paper coated without a stabiliser.
- Superior performance when compared to against ++ thermal paper coated without a stabiliser.

#### **Claims**

- 1. Composition comprising
- a) a colour former compound,
- b) a developer, which is different from the stabilizer used as component c),
- c) a stabilizer, selected from the group consisting of compounds having the formulae I, II and III,

and 
$$R_{1} = S_{0} = N + CNH_{0} +$$

wherein

 $R_1$  stands for unsubstituted or substituted phenyl or naphthyl,  $C_1$ - $C_{20}$ alkyl,  $C_3$ - $C_{10}$ cycloalkyl, wherein the carbon chains of the alkyl (i.e. at least two carbon atoms) and cycloalkyl groups may be interrupted by -O-, -S-, -NH-radicals, or unsubstituted or substituted aralkyl having from seven to twelve carbon atoms,

 $R_2$  stands for hydrogen, unsubstituted or substituted phenyl, naphthyl,  $C_1$ - $C_{20}$ alkyl, unsubstituted or substituted aralkyl having from seven to twelve carbon atoms, or  $R_2$  stands for  $-R_3$ -B-R<sub>4</sub>, in which  $R_3$  stands for phenylene or naphthylene, in particular for o-, m- or p-phenylene, preferably p-phenylene, or 1,2; 2,3; 1,4 or 1,5-naphthylene, preferably 1,5-naphthylene, and wherein B stands for  $-O-SO_2$ -,  $-SO_2-O$ -,  $-NH-SO_2$ -,  $-SO_2-NH$ -,  $-S-SO_3$ -, -O-CO-, -O-CO-NH-, -NH-CO-, -NH-CO-O-, -S-CO-NH-, -S-CS-NH-,  $-CO-NH-SO_2$ -, -O-CO-,  $-NH-SO_2$ -, -NH-CO-, -S-, -CO-, -S-, -C-, -C-, -S-, -C-, -S-, -C-, -S-, -C-, -C-, -S-, -C-, -C-, -C-, -C-, -C-, -C-, -C-, -C-, alkyl, -C-, -C-, alkyl, -C-, -C-, alkyl, -C-, -C-, alkoxy, halogen-substituted -C-, -C-, alkoxy, preferred Substituted -C-, -C-, alkoxy, preferred Substituted -C-, -C-, alkoxy, preferred Substituteds are -C-, alkoxy, preferred Substitutents are -C-, alkoxy, preferred Substitutents

 $C_4$  alkyl and halogen, in particular preferred are phenyl which is unsubstituted or substituted by  $C_1$ - $C_8$  alkyl, halogen-substituted  $C_1$ - $C_8$  alkyl,  $C_1$ - $C_8$  alkyl,  $C_1$ - $C_8$  alkoxy-substituted  $C_1$ - $C_8$  alkoxy or halogen, and unsubstituted naphthyl, more preferred are phenyl which is unsubstituted or substituted by  $C_1$ - $C_4$  alkyl or halogen, and naphthyl, especially phenyl which is unsubstituted or substituted by  $C_1$ - $C_4$  alkyl, benzyl, unsubstituted, preferred, or substituted one to three times by  $C_1$ - $C_8$  alkyl, halogen-substituted  $C_1$ - $C_8$  alkoxy-substituted  $C_1$ - $C_8$  alkoxy, halogen-substituted  $C_1$ - $C_8$  alkoxy or halogen, preferred is unsubstituted benzyl, or  $C_1$ - $C_2$  alkyl, preferably  $C_1$ - $C_8$  alkyl, more preferred benzyl, which can be unsubstituted, preferred, or substituted one to three times by, for example,  $C_1$ - $C_8$  alkoxy, halogen, preferred halogen-substituted  $C_1$ - $C_8$  alkyl, more preferred halogen-substituted  $C_1$ - $C_8$  alkyl, phenyl or naphthyl, preferred phenyl-substituted  $C_1$ - $C_8$  alkyl, or naphthyl-substituted  $C_1$ - $C_8$  alkyl,

A represents a multivalent group having a valency of 2, 3 or 4, n represents an integer of 2, 3 or 4, and X stands for oxygen or sulphur,

 $Y_1$  stands for a heterocyclic ring having from two to seven carbon atoms and from 1 to three atoms selected from the group consisting of oxygen, nitrogen and sulphur, which can be substituted one to three times with unsubstituted or substituted phenyl,  $C_1$ - $C_2$ 0 alkyl,  $C_1$ - $C_3$ 0 alkoxy, halogen or  $-SO_2R_6$ ,  $R_6$  stands for phenyl, which may be substituted one to three times with  $C_1$ - $C_4$ 0 alkyl, wherein the total number of carbon, oxygen, sulphur and nitrogen atoms of the heterocyclic ring is from 5 to 9,

and wherein the amount of the stabilizer is less than 5% by weight, based on the total weight of the composition.

- 2. Heat-sensitive recording material comprising:
- a substrate sheet, and
- a heat-sensitive coloured image-forming layer formed on the surface of the substrate sheet and comprising the composition of claim 1.

3. Use the composition of claim 1 as heat-sensitive coloured image-forming layer for the manufacture of a heat-sensitive recording material.

#### **Abstract**

Composition for heat sensitive recording material

- a) a colour former compound,
- b) a developer, which is different from the stabilizer used as component c),
- c) a stabilizer, selected from the group consisting of compounds having the formulae I, II and III,

wherein the amount of the stabilizer is less than 5% by weight, based on the total weight of the composition,

and a heat sensitive recording material comprising this composition and the use of this composition as heat-sensitive coloured image-forming layer in heat-sensitive materials.

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:	٠
☐ BLACK BORDERS	
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES	
☐ FADED TEXT OR DRAWING	
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING	
☐ SKEWED/SLANTED IMAGES	
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS	
☐ GRAY SCALE DOCUMENTS	
☐ LINES OR MARKS ON ORIGINAL DOCUMENT	
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY	

## IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.